

CLAIMS

What is claimed is:

- 1 1. A motor boat comprising:
2 a V-drive transmission;
3 a center console, said center console comprising a steering wheel engaged
4 thereon; and
5 a driver's seat positioned sternward with respect to said center console.
- 1 2. The motor boat of claim 1, wherein said driver's seat is adjustable elevation-wise.
- 1 3. The motor boat of claim 1, wherein said driver's seat is at least 20 inches from the
2 floor of said motor boat.
- 1 4. The motor boat of claim of claim 1 wherein said driver's seat is 20-40 inches from the
2 floor of the boat.
- 1 5. The motor boat of claim 4 wherein said driver's seat is 25-35 inches from the floor
- 1 6. The motor boat of claim 1 further comprising a wakeboard tower.
- 1 7. The motor boat of claim 1, wherein the floor of said boat surrounding said center
2 console is substantially the same height, whereby no bumps or raises in the floor exist to
3 trip users of the boat.
- 1 8. The motor boat of claim 1 the space between the sides of the center console and the
2 sides of the boat is 8-28 inches.

1 9. The motor boat of claim 1 the space between the sides of the center console and the
2 sides of the boat is 12-18 inches.

1 10. The motor boat of claim 1 further comprising at least one water fillable ballasts to
2 adjust shape and size of wake.

1
1 11. A motor boat comprising:
2 a V-drive transmission;
3 a center console, said center console comprising a steering wheel engaged
4 thereon;
5 a wakeboard tower with integrated wakeboard racks; and
6 a driver's seat positioned sternward with respect to said center console;
7 wherein said motor boat is configured such that a space of 12-20 inches exists
8 between the port and starboard sides of the boat and the port and starboard sides of said
9 center console, respectively.

1 12. A motor boat comprising:
2 a V-drive transmission;
3 a center console, said center console comprising a steering wheel engaged
4 thereon;
5 a wakeboard tower with integrated wakeboard racks;
6 at least one water fillable ballast; and
7 a driver's seat positioned sternward with respect to said center console, said
8 driver's seat is raised to an elevation of at least 20 inches from the floor of said motor
9 boat such that visibility over the bow of the boat is increased;
10 wherein said motor boat is configured such that a space of 12-20 inches exists
11 between the port and starboard sides of the boat and the port and starboard sides of said
12 center console, respectively.

1 13. The motor boat of claim 12, wherein said driver's seat is raised to an elevation of at
2 least 25 inches from the floor of said motor boat.